

TECHNICAL SPECIFICATION **EKEBOL TILT TRAY BODY: MODEL TFS-2000**

(date of issue: 19 Aug 2019 – Rev D)

1. TRAY

- a. Maximum rated capacity of 3 tonnes.
- b. Length of body to suit the truck.
- c. Width inside coamings is 2170mm. Total width is 2270mm.
- d. Typical loading angle is 10 to 12 degrees, depending on the truck chassis.
- e. Maximum tilt angle: approximately 15 degrees
- f. The body is fully welded, heavy-duty construction with large flat floor of 5 mm steel plate.
- g. Front of body provided with a 600mm high headboard.
- h. The body is tapered at the rear to facilitate easy loading and unloading.
- i. Access steps at front of the body are incorporated in full-length rope rails along both sides of body.
- j. The body is automatically locked to the truck chassis when in road travel mode (tray fully down and fully forward).
- k. The body is mounted on a separate sub-frame, which reduces stresses in the truck chassis.
- l. The tilt-frame is pivoted behind the rear wheels.
- m. Tilt-frame and sub-frame fitted with HDPE slide pads to eliminate metal-to-metal contact, minimising wear.
- n. All moving parts are provided with replaceable bushes and/or grease nipples.
- o. Tow-bar with 50mm ball.

2. HYDRAULICS

- a. The oil tank has a 50 litre capacity and is fitted with a filler-breather cap.
- b. The hydraulic pump is attached to the gearbox mounted PTO.
- c. A 3-spool hydraulic control valve with inbuilt pressure relief valve (to protect against overloads) is utilized.
- d. A low pressure return oil filter is mounted on the oil tank and has an easily replaceable cartridge.
- e. Grade of filtration: 10 micron.
- f. The tilt rams are provided with an over-centre type safety valve.
- g. High pressure hoses conform to SAE100 R2T.
- h. The hydraulic hoses for the winch are protected by a plastic hose chain which runs in a track on the tilt frame.

3. CONTROLS

- a. Cable or vacuum operated PTO controls mounted in the cab.
- b. Hydraulic controls are located on left side of chassis, behind the rear wheels.
- c. Dead-man type levers are provided with the following functions: Winch (in/out); Tilt (up/down); Slide (on/off).

EKEBOL

Tough - Reliable - Built to Last

4. WINCH

- a. Hydraulic Sepson planetary drive winch with 3.8 tonnes single line pull (8,300lbs).
- b. Winch provided with 20 metres of 10mm diameter, 6x36 IWRC Grade 1770 wire rope.
- c. The end of the wire rope has a spliced eye/thimble.
- d. The winch is fitted with a manually operated dog clutch to allow free-spooling of drum from the winch only (remote handles not included).

5. ELECTRICS

- a. Two Hella LED combination rear lamps (stop, tail, turn and reverse) are mounted at the rear of the body.
- b. Three LED clearance lights mounted on each side of the body.
- c. A 7 pole trailer socket is fitted near the tow ball.

6. MISCELLANEOUS

- a. Two plastic mudguards with rubber mud-flaps at rear.

7. PAINTING

- a. All tilt slide equipment, underside of body and floor plate is painted in Protec Paraloc satin black. The remainder is delivered prime-coated.

8. DELIVERY

- a. All units are delivered fitted to the truck chassis and in good working order.

NOTES

- a. **The rated capacities are for the tilt-slide equipment only, NOT THE VEHICLE CAPABILITY.** Actual legal payload will depend on permitted axle loadings in your state.
- b. Suitable for most forward control cab-chassis, with a GVM of 6 to 8 tonnes and with a wheelbase between 3.6 metres and 4.6 metres.
- c. Ekebol Pty Ltd is continually striving to improve and update our product range. We reserve the right to change materials and specification without notice. Specifications are correct at the time of printing but may change without notice.